

Master Brake Disk Removal Tool Kit



Information

- 4 Piece female adaptors.
- 12 Piece male adaptors.
- The brake disk removal tool is ideal for damage-free, smooth removal of the brake disk especially if it is stuck and hammering is not possible.

Precautions

- Always wear safety gear.
- Working in a clean and safe environment.
- This task should be carried out by trained personnel.
- Make sure to consult manufacturers manual.
- Do NOT use with air tools.

Contents

4 pieces female adaptors (Japanese Vehicles):
2PC M12 X P1.25.
2PC M12 X P1.5.

12 pieces male adaptors (Euro Vehicles):
2PC M12 X P1.25.
2PC M12 X P1.5.
2PC M12 X P1.75.
2PC M14 X P1.25.
2PC M14 X P1.5.
2PC M16 X P1.5.

Instructions

Step 1

Select the correct size wheel hub bolt (items A) and screw into the wheel hub.



Step 2

Position the the brake removal bar (item B) into the slots in the brake bolts and place the hook bar (item C) over the brake disk.

Tighten the wheel hub bolt (item A) by hand.



Step 3

Hold the hook bar (item C) in place, now tighten the threaded bar (item D) with a ratchet and socket/spanner until the brake disc comes off the wheel hub.

Warranty

If you are unsure on how to use the item please contact us. If it were to fail due to a manufacturing fault or poor workmanship we will repair or replace it. Please contact your local dealer in the event you need to send the item back. You can also make a repair/replacement request on our website and download & complete the form online. Normal wear and tear along with misuse will void any warranty. Consumables are not covered under warranty.

www.welzh.com

Limited **12 month** warranty



Welzh Werkzeug Ltd
Loanwath Road
Gretna, Scotland
DG16 5HD
+44 (0)1461 700120